

**W1****« Stepless » Ear Clamp****Mild steel****« Stepless » Ear Clamp W1**

<b>Information</b>	<b>Ø Nominal mm</b>	<b>Ø Application min. max.</b>	<b>Ref.</b>	<b>H max. mm</b>	<b>S (mm)</b>	<b>a ± 0,15</b>	<b>Box Quantity</b>	<b>Packing</b>
This clamp was designed for use in assembly lines due to the fast and easy locking system. It is normally mounted where a fixed diameter clamp is required and the application zone is difficult to access. It is particularly useful in low to medium pressure applications and for air transfer. Once this clamp has been mounted it is tamper-proof.	10,0	8,3 9,5	03030752	14,0	0,6	7	1000	8000
	13,3	10,8 12,8	03030760	17,0	0,6	7	1000	8000
	15,7	13,2 15,2	03030779	20,1	0,6	7	1000	5000
	17,5	14,3 17,0	03030787	22,5	0,8	7	1000	5000
	17,8	14,6 17,3	03030795	22,5	0,8	7	1000	5000
	18,5	15,3 18,0	03030808	23,5	0,8	7	1000	4000
	20,5	17,3 20,0	03030816	26,0	0,8	7	500	3000
	29,5	26,3 29,0	03030824	35,5	0,8	7	500	3000
	31,6	28,4 31,1	03030832	37,5	0,8	7	500	2000
	39,6	36,4 39,1	03030840	45,5	0,8	7	500	2000
	40,5	37,3 40,0	03030859	46,5	0,8	7	500	1000
	45,5	42,3 45,0	03030867	51,5	0,8	7	200	400
	47,0	43,8 46,5	03030875	53,0	0,8	7	200	400
	51,5	48,3 51,0	03030883	57,5	0,8	7	100	500
52,5	49,3 52,0	03030891	58,5	0,8	7	100	500	
65,5	62,3 65,0	03030904	71,5	0,8	7	100	500	

\* This clamp is also available in W4 (AISI 304) material upon request.

**W1 Materials**

**Band:**  
Mild Steel Dx51D + AZ 150  
(UNI EN 10215)

