

**W3**

12mm S-band Worm-drive Hose clip

DIN: 3017 Heavy series

Asfa-S W3 Hose Clip (12mm bandwidth)

Information	Ø Application mm	Reference W3	L	s +0,1 0	h	a ± 0,4 0,2	b max.	Max. Values* Torque Nm	Max. Values* Pressure (Bars)	Box Quantity	Packing
The ASFA -S W3 hose clip combines an innovative housing and a sturdy 12mm band (compared with 9mm in the light version) which together make this a high-performance hose clip. The cold-formed stamped band thread, smoothed on the underside, combined with the beveled band edges protects the hose from any damage. Manufactured in its entirety in AISI-430 stainless steel, the ASFA-S W3 is a very attractive clip which complies fully with the DIN 3017 norm and also with the RoHs directive EU 2002/95/EC dated 1st July 2006. It is especially recommended for use in automotive, agricultural and fluid transfer applications.	16-27	03016209	29,6	0,8	11	12,2	18	4,2	45	50	400
	20-32	03016217	29,6	0,8	11	12,2	18	5,2	45	50	400
	25-40	03016225	29,6	0,8	11	12,2	18	5,2	40	50	400
	30-45	03016233	29,6	0,8	11	12,2	18	5,2	35	50	400
	32-50	03016241	29,6	0,8	11	12,2	18	6,0	35	50	400
	40-60	03016250	29,6	0,8	11	12,2	18	6,0	30	50	400
	50-70	03016268	31,6	0,8	11	12,2	18	6,8	25	50	400
	60-80	03016276	31,6	0,8	11	12,2	18	6,8	20	50	50
	70-90	03016284	31,6	0,8	11	12,2	18	6,8	17	50	50
	80-100	03016292	31,6	0,8	11	12,2	18	6,8	14	25	200
	90-110	03016305	31,6	0,8	11	12,2	18	6,8	12	25	200
	100-120	03016313	31,6	0,8	11	12,2	18	6,8	10	25	200
	110-130	03016321	31,6	0,8	11	12,2	18	6,8	8	25	25
	120-140	03016330	34,6	0,8	11	12,2	18	6,8	7	25	25
	130-150	03016348	34,6	0,8	11	12,2	18	6,8	6	25	25
	140-160	03016356	34,6	0,8	11	12,2	18	6,8	5	25	25
	150-170	03016364	34,6	0,8	11	12,2	18	6,8	4	25	25
160-180	03016372	34,6	0,8	11	12,2	18	6,8	3	25	25	
170-190	03016380	34,6	0,8	11	12,2	18	6,8	2	10	10	
180-200	03016399	34,6	0,8	11	12,2	18	6,8	2	10	10	
190-210	03016428	34,6	0,8	11	12,2	18	6,8	1,8	10	10	
200-220	03016436	34,6	0,8	11	12,2	18	6,8	1,8	10	10	
210-230	03016444	34,6	0,8	11	12,2	18	6,8	1,6	10	10	
220-240	03016452	34,6	0,8	11	12,2	18	6,8	1,6	10	10	

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

Patented Worldwide.

W3 Materials

Screw:

Stainless steel
(AISI-430)

Band and housing:

Stainless steel X6Cr17
(DIN 1.4016)
(AISI-430)

